

信頼性試験結果/Reliability Test Result

Product	LED
Package	SMD
Series	SML522BU1W

1 試験結果(Test Result)

<u>1.試験結果(Test</u>					_
試験項目	参考規格	試験条件	n	Pn	
Test Items	Reference STD	Test Condition	(pcs)	(pcs)	
半田耐熱 Solder Heat Resistance for Reflow Soldering	J-STD-020D-01	リフローピ−ク温度:260°C 10秒 220°C以上60秒 プルヒート :140°C~180°C 60秒 リフロー回数 :2回 Prtreatment:Temperature Humidity Strage (30°C/70%RH/168hr)	22	0	
		Reflow Peak Temp. : 260°C 10sec Over 220°C/60sec Preheat : 140 to 180°C 60sec Repeat for 2 cycles			
半田付性 Solderbility	JESD22-B102E	ロジン系フラックスに5±1秒浸漬し、245±5°Cの Pbフリー半田槽で製品裏面を3±0.5秒浸漬 Immerse into rosin flux for 5±1sec,and the device for 3±0.5sec into Pb-free solder bath at 245±5°C	22	0	*1
落下 Free Drop	JEITA ED-4701 A-124	高さ:75cm 楓板上:3回 H=75cm Maple Boad:3 times	22	0	
振動		100~2000Hz 98.1m/s ² X,Y,Zの各方向 2時間			
Vibration	A-121	100~2000HZ 98.1m/s 入,1,20分音分词 Z時间 100~2000Hz 98.1m/s ² 2hours each on each direction of X.Y.Z	22	0	
温度サイクル Thermal Cycle	JESD22-A104E	Ta=Tstg Min.°C(30min.) ∼ Tstg Max.°C(30min.)100cycle	22	0	
高温放置 High Temperature Strage	JESD22-A103E	Ta=Tstg Max.+5°C/-0°C 1000hrs	22	0	
高温高湿放置 High Temperature High Humidity Strage	JEITA ED-4701 B-121	Ta=85±2°C 85±5%RH 240hrs	22	0	
低温放置 Low Temperature Strage	JESD22-A119A	Ta=Tstg Min.±5°C 1000hrs	22	0	
動作寿命 Load Life	JESD22-A108D	Ta=25±5°C IF=IFMAX 1000hrs <単色点灯とする>	22	0	

2 測定項目及び故障判定基準(Failure Criteria)

<u> 2.別足頃日及い以降刊足季年</u>	(Tallure Officeria)		
測定項目	測定条件	故障判定基準	
Items	Condition	Criteria	
光度 IF=5mA		初期値の60%	
Luminous Intensity	11 –511174	60% of the initial value	
順方向電圧	IF=5mA	初期値に対する変化率±10%	
Forward Voltage	IF-SIIIA	Changing rate of $\pm 10\%$	
逆方向電流	VR=VR Max.	規格最大値	
Reverse Current	VK-VK Wax.	Maximum of specification	
外観	目視	著しい変化のないこと	
Physical	Visual Check	No outstanding change in physical	

*1	半田付性	電極部の95%以上が半田で覆われていること	ĺ
	Solderbility	More than 95% of the electrode must be covered with solder.	l

[※]当データは、特定Lotの実力値であり保証値ではありません。 ※This data is actual value from specific lot and is not guaranteed.

Notes

- 1) The information contained herein is subject to change without notice.
- Before you use our Products, please contact our sales representative and verify the latest specifications:
- 3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors. Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Poducts beyond the rating specified by ROHM
- 4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
- 5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
- 6) The Products are intended for use in general electronic equipment (i.e. AV/OA devices, communication, consumer systems, gaming/entertainment sets) as well as the applications indicated in this document.
- 7) The Products specified in this document are not designed to be radiation tolerant.
- 8) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, servers, solar cells, and power transmission systems.
- 9) Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
- 10) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
- 11) ROHM has used reasonable care to ensur the accuracy of the information contained in this document. However, ROHM does not warrants that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
- 12) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting non-compliance with any applicable laws or regulations.
- 13) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
- 14) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/