© Copyright 2005. IPC, Bann	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.							
	IPC Web Site for Information on IPC-1752 Standard Form Ty http://www.ipc.org/IPC-175x Distribu			* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materia					als and Mfg Information			
Supplier Information												
ompany name* Company unique ID				Unique ID Authority					Response Date*			
onsemi	mi							2023-06-08				
Contact Name	Title - Contact			1	Phone - Contact*				Email - Contact*			
Product-Env-Stewards	act-Env-Stewards Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
uthorized Representative* Title - Representative				Phone - Representative*				Email - Representative*				
Product-Env-Stewards Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr	Item Number	Mfr Item Name			Effective Date	Version	N	Manufacturing Site		Weight*	UOM	Unit Type
NCF	135AMT040TBG 500 mA, Very Low CMOS Voltage Reg		v Dropout Bias R gulator	Rail	2023-06-08		1	ГН6		10.02	mg	Each
Manufacturing Proccess Information												
Terminal Plating / Grid Array Material	ng / Grid Array Material Terminal Base Alloy J-		STD-020 MSL I	Rating	Peak Proc	ess Body Te	emperatur	re Max Time at Peak	Temperat	ture Numb	er of Reflow Cy	cles
Matte Tin (Sn) - annealed CU Alloy 1					260		С	30	secon	nds 3		
Comments												
level 1 - maximum time at peak temperature durin	g soldering is 10-3	0 seconds										
For more information regarding material composit	ion please refer to	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed			
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth				
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of			
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.								
Exemption List Version	EL-2011/534/EU							
Declaration Signature								
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the			
Supplier Digital Signature Ra	stislav Drska	Le						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight Unit of Measure Level Substance		Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.48	mg	Supplier	Silicon (Si)	7440-21-3		0.48	mg
Die Attach	0.04	mg	Supplier	Isobornyl Methacrylate	7534-94-3		0.0024	mg
			Supplier	Silver (Ag)	7440-22-4		0.0326	mg
			Supplier	Isobornyl Acrylate	5888-33-5		0.0024	mg
			Supplier	Misc.	Proprietary Data		0.0002	mg
			Supplier	Tricyclo[5.2.1.02,6]decanedimethanol Diacrylate (C18H24O4)	42594-17-2		0.0024	mg
Lead Frame	4.16	mg	Supplier	Silver (Ag)	7440-22-4		0.0416	mg
			Supplier	Tin (Sn)	7440-31-5		0.0104	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0092	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0104	mg
			Supplier	Copper (Cu)	7440-50-8		4.0884	mg
Mold Compound-Black	5.09	mg	Supplier	Epoxy resins	129915-35-1		0.2545	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.2545	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0204	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.1171	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		4.3265	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.1171	mg
Plating	0.2	mg	Supplier	Tin (Sn)	7440-31-5		0.2	mg
Wire Bond - Au	0.05	mg	Supplier	Gold (Au)	7440-57-5		0.05	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).