	CONNECTING CONVECTING INDUSTRIES*	IPC, Bannockt	ourn, Illinois. A	Il rights reserved u ntions.	nder both	This docum level parts, t	ent is a declaration	ion of the succession of the s	ubstances v s all lower	within the manufactur level materials for w	er listed i hich the n	tem. Note: i nanufacturer	f the item is an as has engineering	sembly with lower responsibility.	
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
Supplier	Information														
Company name* Company			Company un	any unique ID			Unique ID Authority				Response Date*				
onsemi												2023-06-06			
Contact Na	me	Title - Contact				Phone - Contact*				Email - Contact*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Authorized	Representative*	Title - Representative				Phone - Representative*			Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Item		Number Mfr Item Name				Effective Date	e Version	N	Ianufacturing Site		Weight*	UOM	Unit Type	
		2SK2394-7-TB-E NCI		NCH J-FET		2023-06-06	CNG		-	11.65	mg	Each			
Manufac	turing Proccess Informa	ation													
	Terminal Plating / Grid Array Material Te			erminal Base Alloy J-STD-020 MSI		L Rating	Peak Process Body Temperature		e Max Time at Peak	Temperat	ure Numb	per of Reflow Cyc	les		
contains Bi CU Alloy			CU Alloy	y 1			260 C 30			seconds 3					
Comments															
evel 1 - ma	ximum time at peak temperat	ure during sol	Idering is 10-3	0 seconds											
For more in	nformation regarding material	l composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU												
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	0.11	mg	Supplier	Silicon (Si)	7440-21-3		0.11	mg		
Lead Frame	2.6	mg	Supplier	Silver (Ag)	7440-22-4		0.039	mg		
			Supplier	Chromium (Cr)	7440-47-3		0.0023	mg		
			Supplier	Manganese (Mn)	7439-96-5		0.0195	mg		
			Supplier	Silicon (Si)	7440-21-3		0.0073	mg		
			В	Nickel (Ni)	7440-02-0		1.0187	mg		
			Supplier	Iron (Fe)	7439-89-6		1.4071	mg		
			Supplier	Copper (Cu)	7440-50-8		0.1058	mg		
			Supplier	Phosphorus (P)	7723-14-0		0.0003	mg		
Mold Compound-Black	8.7	mg		Brominated epoxy resin	proprietary data		0.2175	mg		
			В	Antimony Trioxide (Sb2O3)	1309-64-4		0.1392	mg		
			Supplier	Carbon Black (C)	1333-86-4		0.0435	mg		
			Supplier	Fused Silica (SiO2)	60676-86-0		6.1248	mg		
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		2.175	mg		
Plating	0.22	mg	В	Bismuth (Bi)	7440-69-9		0.0013	mg		
			Supplier	Tin (Sn)	7440-31-5		0.2187	mg		
Wire Bond - Au	0.02	mg	Supplier	Gold (Au)	7440-57-5		0.02	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).