


FC0H105ZFTBR44-SS

Aliases (USCFC00H105ZZE)

FC, Supercapacitors, SMD Can, 1F, -20/+80%, 5.5 VDC, V-Chip



Click here for the 3D model.

Dimensions	
D	21mm +/-0.5mm
L	10.5mm MAX
W	21.6mm +/-0.2mm
S	10mm NOM
G	0mm +0.3/-0.1mm
LT1	1.4mm +/-0.1mm
LT2	7mm +1mm

Packaging Specifications		
Lead	V-Chip	
Packaging	T&R, 380mm	

General Information	
Series	FC
Description	Surface Mount Double Layer Capacitor
Features	Ultra Low ESR, High Power Pulse
RoHS	Yes
AEC-Q200	No
Component Weight	6.7 g

Specifications				
Capacitance	1F			
Capacitance Tolerance	-20/+80%			
Voltage DC	5.5 VDC, 4.2 VDC (Holding Voltage)			
Temperature Range	-25/+70°C			
Rated Temperature	70°C			
Resistance	7000 mOhms (1kHz)			
Discharge Current	1.5 mAmps (30 Minutes After Charging)			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.